

Observing the Consistency of Distributed Systems

Deepthi Akkoorath¹ Viktória Fördös² Annette Bieniusa¹

¹University of Kaiserslautern


²Erlang Solutions

Erlang Workshop '16




SYNC
FREE


Weakly Consistent Geo-replicated System




Weakly Consistent Geo-replicated System




Weakly Consistent Geo-replicated System




Weakly Consistent Geo-replicated System



Weakly Consistent Geo-replicated System



Weakly Consistent Geo-replicated System



Problem

Application built on EC databases may **tolerate some divergence**.
But large divergence may result in SLA violations or
unsatisfactory client experiences.

- How to quantify divergence?
- How to monitor divergence?

Divergence

- Measure of how different the state of a replica compared to others
- Number of missing updates
- Require information about all updates in other replicas
- Not practical to measure

Divergence

- Measure of how different the state of a replica compared to others
- Number of missing updates
- Require information about all updates in other replicas
- Not practical to measure

Goal

- Estimate divergence from local knowledge

Staleness

- How old is the data?
- \approx Time elapsed from last synchronisation
- Only **potential** staleness

Antidote

- Georeplicated Key-value store
- Written in Erlang
- Weak consistency (Eventual/Causal)
- Conflict-free Replicated Data Types for convergence

WombatOAM

- An operation and maintenance tool
- For systems running on BEAM virtual machines

Measuring Staleness in Antidote

Consistency protocol: Cure

- Based on timestamps from real clocks such as NTP
- Maintains a vector of timestamps
- Eg:- $[\{dc_1, 10\}, \{dc_2, 11\}]$
 - Received all updates with timestamps ≤ 10 from dc_1
 - Received all updates with timestamp ≤ 11 from dc_2

Measuring Staleness in Antidote

Consistency protocol: Cure

- Based on timestamps from real clocks such as NTP
- Maintains a vector of timestamps
- Eg:- $[\{dc_1, 10\}, \{dc_2, 11\}]$
 - Received all updates with timestamps ≤ 10 from dc_1
 - Received all updates with timestamp ≤ 11 from dc_2
- Staleness = difference between local timestamp and the observed

Measuring Staleness in Antidote

- An erlang process running in each node
- Periodically probes vector clock and calculates staleness
- Store result in Exometer histogram
 - Exometer - package for instrumenting Erlang code

Monitoring Divergence

- WombatOAM plugin for antidote
 - Read metrics stored in Exometer
 - Communicates to Wombat
- WombatOAM
 - Configure threshold values
 - Exposes the maximum and median values
 - Raise alarms when divergence exceeds the threshold

DEMO

localhost:8080/#/topo

WombatOAM™

Topology Metrics Notifications Alarms Services Help

admin


Node Info General Information Add Node Node Graph

OTP APN 181 01 R16B03



You can choose between different functionalities using the top bars.
Click on a family or a node to view its details.

Results



Questions?

- Antidote <https://antidotedb.org>
- WombatOAM <https://www.erlang-solutions.com/products/wombat-oam.html>
- akkoorath@cs.uni-kl.de

Thank You!